

Claims:

- 1 1) A circuit for detecting and routing a telephone ringing signal, comprising:  
2 an input terminal for receiving a telephone ringing signal;  
3 a frequency filter for selecting signals of a specific frequency from said  
4 ringing signal; and  
5 a switch, responsive to said selected signals, for routing said telephone  
6 ringing signal.

7  
1 2) The circuit of claim 1 comprising two bandpass filters.

1 3) The circuit of claim 1 comprising two switches.

1 4) The circuit of claim 1 wherein said switch is an analog switch.

1 5) The circuit of claim 1 further comprising a capacitor for removing noise of  
2 said specific frequency.

1 6) The circuit of claim 1 further comprising a speaker.

1 7) A method of detecting and routing an incoming ringing signal for a telephone,  
2 comprising the steps of:  
3 splitting off a portion of the incoming ringing signal;  
4 checking if a desired characteristic is present in the portion of the incoming  
5 ringing signal; and  
6 routing the incoming ringing signal based on whether the characteristic is  
7 present.

1 8) The method of claim 7 wherein said characteristic is frequency.

1 9) The method of claim 7 wherein said characteristic is wavelength.

1 10) The method of claim 7 wherein said characteristic is a wave packet generated  
2 by a computer server.

1 11) The method of claim 7 wherein said step of checking checks for the presence  
2 of a plurality of characteristics.

1 12) A system for detecting and routing an incoming signal, comprising:  
2 a frequency filter for selecting signals of a specific frequency from said  
3 incoming signal;  
4 a capacitor for removing brief intervals of said selected signals;

5 a switch responsive to said selected signals for routing said incoming signal;  
6 and  
7 a speaker.

1 13) The system of claim 12 comprising two frequency filters.

1 14) The system of claim 12 comprising two switches.

1 15) The system of claim 12 wherein said switch is an analog switch.

1 16) A system for detecting and routing an incoming signal, comprising:  
2 an input/output device for receiving and transmitting the incoming signal;  
3 a CPU for processing the incoming signal;  
4 logic for analyzing the processed signal;  
5 an amplifier for amplifying a ringing signal; and  
6 a speaker for outputting said amplified signal.

1 17) The system of claim 16 wherein said input/output device is a soundcard.

1 18) The system of claim 16 wherein said CPU is part of a personal computer.

1 19) The system of claim 16 wherein said logic is in software.

- 1 20) The system of claim 16 wherein said input/output device is an analog to
- 2 digital converter.